

**CORRIGENDUM**

With reference to the NIT no.-CUJ/EE/Road constt./32/2019-20/37 dated: 26.12.2019, the BOQ enclosed with the tender is only for 100meter.The revised BOQ for the 430 meter length is as below. This will replace the original BOQ of the tender .The date of submission of tender has been changed to 13.12.2019 instead of 10.12.2019.

All interested tenderers are requested to use this revised BOQ.

S/d  
Registrar (I/c)

**Revised BOQ**

| Sl.No | DSR-18 | Description of Items  | Qty | Unit | Rate (for 100 m) | Amount |
|-------|--------|---|-----|------|------------------|--------|
| 1     | 2.6.1  | Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge. All kinds of soil  | 108 | m3   |                  |        |
| 2     | 2.7.1  | Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-incharge.  | 84  | m3   |                  |        |
| 3     | 2.2.1  | Earth work in rough excavation, banking excavated earth in layers not exceeding 20cm in depth, breaking clods, watering, rolling each layer with ½ tonne roller or wooden or steel rammers, and rolling every 3rd and top-most layer with power roller of minimum 8 tonnes and dressing up in embankments for roads, flood banks, marginal banks and guide banks or filling up ground depressions, lead upto 50 m and lift upto 1.5 m : All kinds of soil | 195 | m2   |                  |        |
| 4     | 2.8.1  | Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.All kinds of soil.   | 36  | m3   |                  |        |

|   |         |   |          |    |  |  |
|---|---------|---|----------|----|--|--|
| 5 | 2.9.1   | Excavation work by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drains (not exceeding 1.5m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directed, within a lead of 50 m. Ordinary rock                                       | 24       | m3 |  |  |
| 6 | 16.1    | Preparation and consolidation of sub grade with power road roller of 8 to 12 tonne capacity after excavating earth to an average of 22.5 cm depth, dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earthwith lead upto 50 metres.   | 400      | m2 |  |  |
| 7 | 16.3.3  | Supplying and stacking at site. 53 mm to 22.4 mm size stone aggregate   | 80       | m3 |  |  |
| 8 | 16.3.10 | Supplying and stacking at site. Moorum cum 807.80<br>16.4 Laying, spreading and   | 79.<br>2 | m3 |  |  |
| 9 | 16.4    | Laying, spreading and compacting stone aggregate of specified sizes to WBM specifications in uniform thickness, hand picking, rolling with 3 wheeled road/vibratory roller 8-10 tonne capacity in stages to proper grade and camber, applying and brooming requisite type of screening / binding material to fill up interstices of coarse aggregate, watering and compacting to the required density . | 80       | m3 |  |  |

|               |        |   |                        |    |  |  |
|---------------|--------|---|------------------------|----|--|--|
| 10            | 2.3.1  | Banking excavated earth in layers not exceeding 20 cm in depth, breaking clods, watering, rolling each layer with ½ tonne roller, or wooden or steel rammers, and rolling every 3rd and top-most layer with power roller of minimum 8 tonnes and dressing up, in embankments for roads, flood banks, marginal banks, and guide banks etc., lead upto 50 m and lift upto 1.5 m : All kinds of soil | 40                     | m3 |  |  |
|               |        |   | Total for 100 m length |    |  |  |
|               |        |   | Total for 430 m length |    |  |  |
| 11            | 19.6.7 | Providing and laying non-pressure NP2 class (light duty) R.C.C. pipes with collars jointed with stiff mixture of cement mortar in the proportion of 1:2 (1 cement : 2 fine sand) including testing of joints etc. complete : 600 mm dia. R.C.C. pipe  | 10                     | m  |  |  |
| 12            |        | Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:4:8 (1 Cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size)  | 3                      | m3 |  |  |
| Total (in Rs) |        |   |                        |    |  |  |

Amount in Word:-

**Name & Signature of Firm with seal**