

BOQ

Sl.No	DSR-2014	Items	Qty	Unit	Rate	Amount
1	NDSR	FULL HEIGHT PARTITION-SOLID Providing and fixing in position full height partition having overall thickness of 3" approx. made out of vertical and horizantle frame work of 2 1/2"x2 1/2" pinewood member(1st class) at maximum distance of 2'-0" approx C/C bothway.				
		Fixing 12mm thick commercial Ply on both side with 1.0 mm thick laminated on top in approved shade in groove pattern as per University instruction. Groove to be finished with 12 mm wide SS trip.(All to be completed as per approval of the Engineer-in-charge)	2351.09	Sq.ft		
2	9.6	Providing and fixing 35 mm thick factory made laminated veneer lumber door shutter conforming to IS : 14616 and TADS 15:2001 (Part B), including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws, all complete as per directions of Engineerin-charge and panelling with panels of :				
	9.6.2	12 mm thick pre-laminated particle board (decorative lamination on both sides) grade - 1, medium density flat pressed, three layer particle board FPT - I or graded wood particle board FPTI, conforming to IS : 3087, bonded with BWP type synthetic resin adhesive as per IS : 848 and pre-laminated conforming to IS :	23.4716	m2		
3	9.7.7.2	5.5 mm thick glass panes	16.6205	m2		
4	9.58.1	Providing and fixing ISI marked oxidised M.S. pressed Parliamentary hinges with necessary screws etc. complete :150x125x27x2.80 mm	44	nos.		
5	9.96.2	Providing and fixing aluminium sliding door bolts, ISI marked anodised anodic coating not less than grade AC 10 (as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete :250x16 mm	11	nos.		

6	9.97.2	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :250x10 mm	11	nos.		
7	9.100.1	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :125 mm	22	nos.		
8	9.101.1	Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete with Single rubber stopper	11	nos.		
9	9.84	Providing and fixing aluminium extruded section body tubular type universal (1000 mm), with double speed adjustment with necessary accessories and screws etc. complete. hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701 mm to 1000 mm), with double speed adjustment with necessary accessories and screws etc. complete.	11	nos.		
10	12.51.6	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+ 0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete :Gutter .(600 mm over all girth)	285.2	m		
		0			Total =	

TOTAL AMOUNT IN FIGURE

TOTAL AMOUNT IN WORD

SIGN WITH SEAL